2-Port Mini KVM Switch

1-Port USB, 1-Port PS/2, Audio Support

Part No.: 524612

The INTELLINET NETWORK SOLUTIONS KVM Switch is a 2-port Mini KVM switch with integrated connection cables. Its PS/2 support on the console side allows you to use a PS/2 keyboard and mouse. It allows you to access, control, boot and reboot one PS/2-enabled and one USB enabled computer with only one PS/2 keyboard, mouse and monitor.

Convenient PC selection

Quickly and easily switch between workstations using the hotkey.

Audio Switching Offers an Uninterrupted Multimedia Experience

The audio switching function of this KVM Switch allows you to leverage the multimedia systems on each of your two computers. You can monitor the audio output of each computer without plugging on and off the audio cables.

Zero Cabling Hassles for KVM Users

This KVM Switch saves you cabling troubles with its two pair of 1.2 m (4 ft.) KVM connection cables. In fact, you have zero cabling troubles since you don't have to worry about finding suitable cables to fit — they come attached to the KVM switch!

2-Port Mini KVM Switch

1-Port USB, 1-Port PS/2, Audio Support

Part No.: 524612

Features:

- Operate one PS/2 and one USB computer with one PS/2 keyboard, PS/2 mouse and SVGA monitor
- Simply plug in the attached cables - nothing else required!
- Full keyboard and mouse emulation for error-free booting
- Hotkey commands and LED indicators for computer selection
- Audio output for speaker connection
- No software or power required
- Compatible with all operating systems
- Supports resolutions up to 1920 x 1440 pixels
- Three-Year Warranty

Specifications:

General
» PC connections: 2
» Console connections: 1
» PC port connector 1:
- 1 x USB type-A male (keyboard, mouse)
- 1 x HD15 M (video)
- 1 x 3.5 mm jack (sound card input)
- Integrated connection cable: 1.2 m (4 ft.)
» PC port connector 2:
- 1 x PS/2 (keyboard, mouse)
- 1 x HD15 M (video)
- 1 x 3.5 mm jack (sound card input)
- Integrated connection cable: 1.2 m (4 ft.)
» Console port connectors:
- Keyboard: PS/2
- Mouse: PS/2
- Monitor: HD15 female
- 1 x 3.5 mm jack (speaker output)
» Computer selection:
- Via hotkey
» Video resolution: max. 1920 x 1440
» Video bandwidth: max. 250 MHz
» FCC Class B, CE, RoHS

LEDs
» 1 LED per channel

Environmental
» Plastic housing
» Scan interval: 3 seconds
» Dimensions: 85 (W) x 75 (D) x 26 (H) mm (3.4 x 3 x 1 in.)
» Operating temperature: 0 - 50°C (32 - 122°F)
» Storage temperature: -20 - 60°C (-4 - 140°F)
» Weight: 380 g (13.4 oz.)

Package Contents
» 2-Port Mini KVM Switch
» Quick installation guide

For more information on INTELLINET NETWORK SOLUTIONS products, consult your local dealer or visit www.intellinet-network.com.

Copyright © INTELLINET NETWORK SOLUTIONS

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, use and disclosure of the contents herein are prohibited, unless specifically authorized.